



TECHNICAL DATA SHEET

MAQ01

DS-180

**Drum cylindrical 30L
286x530**

REV.1

16/03/2021

CARACTERISTICS

DIAM.NOM.	286	HEIGHT	530	PRESS. TEST	0,2 bar	PPG CODE	MDT-0011
------------------	-----	---------------	-----	--------------------	---------	-----------------	----------



OPENING	Off-centered	OPENING CHARACTERISTICS	2" + 3/4"
HANDLE	1 plastic handle	HANDLE POSITION	centered
WELDING	electric	WELDING POSITION	Longitudinal
BEAD	2	BEAD POSITION	--

TECHNICAL DATA

TOP	Tinplate DIN EN 10202, with 2,0/2,0 gr/m ² , thickness 0,40mm. stamped. natural aquabased gasket Internal coating : plain - outside coating : gold coating
BODY	Tinplate DIN EN 10202, with 2,0/2,0 gr/m ² , thickness 0,34mm. electrical welding, Internal coating : plain - outside coating : gold coating
BOTTOM	Tinplate DIN EN 10202, with 2,0/2,0 gr/m ² , thickness 0,34mm. natural aquabased gasket Internal coating : plain - outside coating : plain

PALETTISATION

42 or 28pcs/pallet 1000x1200

CARACTERISTIQUES ET TESTS

ISO capacity : 32 L

Pressure test during production : 0,2 bar.

Welding and semailng parameters checked along the production process

UN approval : 1A1/Y1.4/110/**/F/BVT 229316/FS